

3/2 - Way Ball valves



Specificaties

Brand/type	Rub Valves
Maximum temp.	Staal 120°C/RVS 180°C
Minimum temp.	-10°C
Sizes	1/4" - 2"
Lever	Steel/Stainless steel geomet coated
Way of connect.	Female x female x female
Threads	BSP ISO 228
Material	Steel and stainless steel

Size	PN	Description	Thread connection	Code
1/4"	55	Ball valve 3-way T-Bore	Fem x fem x fem	NSH404-02-006
3/8"	55	Ball valve 3-way T-Bore	Fem x fem x fem	NSH404-02-010
1/2"	50	Ball valve 3-way T-Bore	Fem x fem x fem	NSH404-02-013
3/4"	50	Ball valve 3-way T-Bore	Fem x fem x fem	NSH404-02-019
1"	45	Ball valve 3-way T-Bore	Fem x fem x fem	NSH404-02-025
1.1/4"	35	Ball valve 3-way T-Bore	Fem x fem x fem	NSH404-02-032
1.1/2"	35	Ball valve 3-way T-Bore	Fem x fem x fem	NSH404-02-038
2"	35	Ball valve 3-way T-Bore	Fem x fem x fem	NSH404-02-050
1/4"	55	Ball valve 3-way L-Bore	Fem x fem x fem	NSH404-01-006
3/8"	55	Ball valve 3-way L-Bore	Fem x fem x fem	NSH404-01-010
1/2"	50	Ball valve 3-way L-Bore	Fem x fem x fem	NSH404-01-013
3/4"	50	Ball valve 3-way L-Bore	Fem x fem x fem	NSH404-01-019
1"	45	Ball valve 3-way L-Bore	Fem x fem x fem	NSH404-01-025
1.1/4"	35	Ball valve 3-way L-Bore	Fem x fem x fem	NSH404-01-032
1.1/2"	35	Ball valve 3-way L-Bore	Fem x fem x fem	NSH404-01-038
2"	35	Ball valve 3-way L-Bore	Fem x fem x fem	NSH404-01-050
3/8"	63	Ball valve 3-way T-Bore Stainless steel	Fem x fem x fem	NSH406-02-010
1/2"	63	Ball valve 3-way T-Bore Stainless steel	Fem x fem x fem	NSH406-02-013
3/4"	63	Ball valve 3-way T-Bore Stainless steel	Fem x fem x fem	NSH406-02-019
1"	63	Ball valve 3-way T-Bore Stainless steel	Fem x fem x fem	NSH406-02-025
1.1/4"	63	Ball valve 3-way T-Bore Stainless steel	Fem x fem x fem	NSH406-02-032
1.1/2"	63	Ball valve 3-way T-Bore Stainless steel	Fem x fem x fem	NSH406-02-038
2"	63	Ball valve 3-way T-Bore Stainless steel	Fem x fem x fem	NSH406-02-050
3/8"	63	Ball valve 3-way L-Bore Stainless steel	Fem x fem x fem	NSH406-01-010
1/2"	63	Ball valve 3-way L-Bore Stainless steel	Fem x fem x fem	NSH406-01-013
3/4"	63	Ball valve 3-way L-Bore Stainless steel	Fem x fem x fem	NSH406-01-019
1"	63	Ball valve 3-way L-Bore Stainless steel	Fem x fem x fem	NSH406-01-025
1.1/4"	63	Ball valve 3-way L-Bore Stainless steel	Fem x fem x fem	NSH406-01-032
1.1/2"	63	Ball valve 3-way L-Bore Stainless steel	Fem x fem x fem	NSH406-01-038
2"	63	Ball valve 3-way L-Bore Stainless steel	Fem x fem x fem	NSH406-01-050

Description

Full bore 3-way ball valve, with BSP thread(s) on both sides according to ISO 228.
PTFE seals around the ball and double FKM seals around the spindle. All taps have been tested for leak tightness for at least 24 hours.