

Graphite Ring Gasket



Specifications

Brand/type	Graphite gasket
Temp. Range	-200°C - +700°C
Solutions	General usage, liquids, steam, and gaseous applications
Thickness	2mm (standard)
Work pressure	130 bar
Material	Graphite, stainless steel

Size	DN	PN	O.D.	I.D.	Thickness	Pitch	Code
1/2"	15	6	43	22	2mm	-	NSH705-03-015
3/4"	20	6	53	28	2mm	-	NSH705-03-030
1"	25	6	63	35	2mm	-	NSH705-03-025
1.1/4"	32	6	75	43	2mm	-	NSH705-03-032
1.1/2"	40	6	85	49	2mm	-	NSH705-03-040
2"	50	6	95	61	2mm	-	NSH705-03-050
2.1/2"	65	6	115	77	2mm	-	NSH705-03-065
3"	80	6	132	90	2mm	-	NSH705-03-080
4"	100	6	152	115	2mm	-	NSH705-03-100
5"	125	6	182	141	2mm	-	NSH705-03-125
6"	150	6	207	169	2mm	-	NSH705-03-150
8"	200	6	262	220	2mm	-	NSH705-03-200
10"	250	6	318	274	2mm	-	NSH705-03-250
12"	300	6	373	325	2mm	-	NSH705-03-300
14"	350	6	423	368	2mm	-	NSH705-03-350
16"	400	6	473	420	2mm	-	NSH705-03-400
18"	450	6	528	470	2mm	-	NSH705-03-450
20"	500	6	578	520	2mm	-	NSH705-03-500