

Ball valves



Specifications

Brand/type	Rub Valves
Maximum temp.	Steel 170°C/Stainless steel 180°C
Minimum temp.	Steell -40°C/Stainless steel 0°C
Sizes	1/4" - 4"
Lever	Coated geomet
Way of connect.	Female thread
Threads	BSP ISO 228
Material	Nickel, steel and stainless steel

Size	PN	Description	Thread connection	Code
1/4"	40	Ball valve without filter	Female thread	NSH400-06-006
3/8"	40	Ball valve without filter	Female thread	NSH400-06-010
1/2"	40	Ball valve without filter	Female thread	NSH400-06-013
3/4"	40	Ball valve without filter	Female thread	NSH400-06-019
1"	40	Ball valve without filter	Female thread	NSH400-06-025
1.1/4"	40	Ball valve without filter	Female thread	NSH400-06-032
1.1/2"	40	Ball valve without filter	Female thread	NSH400-06-038
2"	40	Ball valve without filter	Female thread	NSH400-06-050
1/2"	30	Ball valve with filter	Female thread	NSH400-05-013
3/4"	30	Ball valve with filter	Female thread	NSH400-05-019
1"	30	Ball valve with filter	Female thread	NSH400-05-025
1.1/4"	30	Ball valve with filter	Female thread	NSH400-05-032
1.1/2"	30	Ball valve with filter	Female thread	NSH400-05-038
2"	30	Ball valve with filter	Female thread	NSH400-05-050
1/4"	40	Ball valve with wing	Female x Male	NSH400-03-006
3/8"	40	Ball valve with wing	Female x Male	NSH400-03-010
1/2"	40	Ball valve with wing	Female x Male	NSH400-03-013
3/4"	40	Ball valve with wing	Female x Male	NSH400-03-019
1"	40	Ball valve with wing	Female x Male	NSH400-03-025
1/4"	40	Ball valve with wing	Female thread	NSH400-02-006
3/8"	40	Ball valve with wing	Female thread	NSH400-02-010
1/2"	40	Ball valve with wing	Female thread	NSH400-02-013
3/4"	40	Ball valve with wing	Female thread	NSH400-02-019
1"	40	Ball valve with wing	Female thread	NSH400-02-025
1/4"	40	Ball valve without filter	Female thread	NSH400-01-006
3/8"	40	Ball valve without filter	Female thread	NSH400-01-010
1/2"	40	Ball valve without filter	Female thread	NSH400-01-013
3/4"	40	Ball valve without filter	Female thread	NSH400-01-019
1"	40	Ball valve without filter	Female thread	NSH400-01-025

1.1/4"	40	Ball valve without filter	Female thread	NSH400-01-032
1.1/2"	40	Ball valve without filter	Female thread	NSH400-01-038
2"	40	Ball valve without filter	Female thread	NSH400-01-050
2.1/2"	40	Ball valve without filter	Female thread	NSH400-01-065
3"	40	Ball valve without filter	Female thread	NSH400-01-075
4"	40	Ball valve without filter	Female thread	NSH400-01-100
1/4"	63	Ball valve stainless steel without lock	Female thread	NSH405-01-006
3/8"	63	Ball valve stainless steel without lock	Female thread	NSH405-01-010
1/2"	63	Ball valve stainless steel without lock	Female thread	NSH405-01-013
3/4"	63	Ball valve stainless steel without lock	Female thread	NSH405-01-019
1"	63	Ball valve stainless steel without lock	Female thread	NSH405-01-025
1.1/4"	63	Ball valve stainless steel without lock	Female thread	NSH405-01-032
1.1/2"	63	Ball valve stainless steel without lock	Female thread	NSH405-01-038
2"	63	Ball valve stainless steel without lock	Female thread	NSH405-01-050
2.1/2"	63	Ball valve stainless steel without lock	Female thread	NSH405-01-065
3"	63	Ball valve stainless steel without lock	Female thread	NSH405-01-075
4"	63	Ball valve stainless steel without lock	Female thread	NSH405-01-100

Description

Full bore nickel plated ball valve, with BSP thread(s) on both sides according to ISO 228. PTFE seals around the ball and double FKM seal around the spindle. All taps have been tested for leak tightness for at last 24 hours.