

Rubber gasket "washer"



Specifications

Brand/type	Washer
Temp. Range	+70°C
Minimum temp.	Steell -40°C/Stainless steel 0°C
Solutions	General usage for water, air and non-aggressive liquids
thickness	3mm (standard)
Material	SBR

Size	DN	PN	O.D.	I.D.	Standard thickness	Code
1/2"	15	10	50	22	3mm	NSH710-01-015
3/4"	20	10	60	28	3mm	NSH710-01-020
1"	25	10	70	35	3mm	NSH710-01-025
1.1/4"	32	10	82	43	3mm	NSH710-01-032
1.1/2"	40	10	92	49	3mm	NSH710-01-040
2"	50	10	107	61	3mm	NSH710-01-050
2.1/2"	65	10	127	77	3mm	NSH710-01-065
3"	80	10	142	90	3mm	NSH710-01-080
4"	100	10	162	115	3mm	NSH710-01-100
5"	125	10	192	141	3mm	NSH710-01-125
6"	150	10	218	169	3mm	NSH710-01-150
8"	200	10	273	220	3mm	NSH710-01-200
10"	250	10	328	274	3mm	NSH710-01-250
12"	300	10	378	325	3mm	NSH710-01-300
14"	350	10	438	368	3mm	NSH710-01-350
16"	400	10	490	420	3mm	NSH710-01-400
18"	450	10	540	470	3mm	NSH710-01-450
20"	500	10	595	520	3mm	NSH710-01-500